The UHD logging facility

Contents

- 1 Application Note Information
- 2 Revision History
- 3 Overview
- 4 Code
- 5 Concepts 5.1 CMake Logging Settings
 - 5.2 Runtime Logging Settings

AN-001 by Michael Dickens

This application note describes the UHD logging facility: compile-time options, runtime options, application usage, and default values ... and how all of these interact.

UHD has 3 primary files associated with logging: log.hpp, log.cpp, and UHDLog.cmake. There are secondary logging files providing an interface to C

There are 7 logging levels; the name and number can be used interchangeably for any logging variable.

UHD Logging Levels

trace debug info warning error fatal off 3 4 6

There are 2 distinct times where logging can be controlled: during compilation per CMake settings, and during runtime via shell environment variables.

There are 10 CMake variables that control logging:

- 6 are boolean: uhd_log_fastpath_disable, uhd_log_console_disable, uhd_log_console_color, uhd_log_console_time, UHD_LOG_CONSOLE_THREAD, and UHD_LOG_CONSOLE_SRC;
- 3 set log levels: uhd_log_min_level, uhd_log_file_level, and uhd_log_console_level;
- 1 sets the default log file: UHD_LOG_FILE.

Each of these variables can be set independently via the CMake commandline or other methods, and override each's default value as set in the UHD CMake scripts. The default values for 2 of these variables depends on whether the CMAKE_BUILD_TYPE is Debug or not, as follows:

UHD CMake Logging Variables and Default Values for different CMAKE_BUILD_TYPE

Default Value

Variable non-Debug Debug UHD_LOG_FILE_LEVEL info UHD LOG CONSOLE LEVEL info debua

Here is a description of the 10 CMake variables the influence logging:

- The variable UHD_LOG_CONSOLE_DISABLE sets whether to disable (if ON) or enable (if OFF) console-based logging; the default is OFF such that console logging is enabled. When set to ON, console-based logging is not compiled into UHD at all, and so any CONSOLE log setting will have no
- The variable UHD_LOG_FASTPATH_DISABLE sets whether to disable (if ON) or enable (if OFF) fastpath logging; the default is OFF such that fastpath logging is enabled. Fastpath logging is used for Extra-fast logging macro for when speed matters; no metadata is tracked, and only the message is displayed. This logging is used for printing the UOSDL characters during streaming to show underrun, overflow, and other situations.
- sequences. By default on Microsoft Windows or Cygwin, colorization is disabled; otherwise it is enabled.
- The variable UHD_LOG_CONSOLE_TIME sets whether to disable (if OFF) or enable (if ON the current timestamp as part of the log message. By default this variable is not set, which means it is OFF. This variable must be set to ON (or the equivalent) for this logging to be enabled.
- The variable UHD_LOG_CONSOLE_THREAD sets whether to disable (if OFF) or enable (if on the thread ID displaying the log as part of the log message. By default this variable is not set, which means it is OFF. This variable must be set to ON (or the equivalent) for this logging to be enabled.
- The variable UHD_LOG_CONSOLE_SRC sets whether to disable (if OFF) or enable (if ON the source code filename and line displaying the log as part of the log message. By default this variable is not set, which means it is OFF. This variable must be set to ON (or the equivalent) for this logging to be enabled.
- The variable UHD_LOG_MIN_LEVEL sets the minimum logging level for any logging functionality. For example, when this variable is set to debug (the default), then trace level debugging will not be available for any logging; only debug and higher (up to fatal) will be available. Setting this variable to off will disable runtime logging, but all enabled logging will still be compiled as part of UHD.
- The variable UHD_LOG_FILE_LEVEL sets the default value for file-based logging. This value can be changed for runtime to any value UHD_LOG_MIN_LEVEL or higher.
- The variable UHD_LOG_CONSOLE_LEVEL sets the default value for console-based logging. This value can be changed for runtime to any value UHD_LOG_MIN_LEVEL or higher.
- The variable UHD_LOG_FILE sets the default file to use for file-based logging. By default this variable is not set, which means that there is no default file to write file-based logging into. If not set during compile-time, then to enable file-based logging the eponymous runtime variable must be set, as noted below.

There are 5 runtime environment variables that control logging. Each of these variables can be set independently via a shell environment, on the commandline, or other methods, and override each's default value as set by the aforementioned CMake variables.

- The variable UHD_LOG_LEVEL sets the minimum logging level for any logging functionality. For example, when this variable is set to debug (the default), then trace level debugging will not be available for any logging; only debug and higher (up to fatal) will be available.
- The variable UHD_LOG_FILE_LEVEL sets the default value for file-based logging. This value can be changed for runtime to any value UHD_LOG_MIN_LEVEL or higher.
- The variable UHD_LOG_FILE sets the file to use for file-based logging. If no log file is set at compile-time or runtime, then no file logging will take place. Any file specified for logging must be able to be opened for writing to (but not necessarily reading from by the UHD process); any existing file will be appended to.
- The variable <code>UHD_LOG_CONSOLE_LEVEL</code> sets the default value for console-based logging. This value can be changed for runtime to any value <code>UHD_LOG_MIN_LEVEL</code> or higher.
- The variable UHD_LOG_FASTPATH_DISABLE sets whether to disable fastpath logging, if it was not disabled at compile-time.